

### JME120HC

Ambient Temp. (°C) (Dry Bulb temp.)	-25	-20	-15	-7	2	7	15	20	25	35	43
Heating Capacity (W) (Outlet Water Temp. 55°C)	3924	5068	6332	6481	6952	7786	8461	9377	10617	11979	13542
Heating Capacity (W) (Outlet Water Temp. 41°C)	4100	5303	6755	6618	8453	9654	10356	12192	13234	13571	14967
Heating Capacity (W) (Outlet Water Temp. 35°C)	4387	5432	6891	7351	9540	10865	11682	12934	14199	14973	16385
Power Input (W) (Outlet Water Temp. 55°C)	2507	2718	2976	2851	2739	2834	2738	2651	2671	2686	2705
Power Input (W) (Outlet Water Temp. 41°C)	2493	2470	2913	2531	2523	2582	2719	2609	2635	2644	2694
Power Input (W) (Outlet Water Temp. 35°C)	2289	2350	2468	2501	2459	2534	2603	2605	2614	2634	2651
COP (Outlet Water Temp. 55°C)	1,57	1,86	2,13	2,27	2,54	2,75	3,09	3,54	3,97	4,46	5,01
COP (Outlet Water Temp. 41°C)	1,64	2,15	2,32	2,61	3,35	3,74	3,81	4,67	5,02	5,13	5,56
COP (Outlet Water Temp. 35°C)	1,92	2,31	2,79	2,94	3,88	4,29	4,49	4,97	5,43	5,68	6,18
Water production(kg/h) (Water Temp. 15°C to 55°C)	84,35	108,94	136,11	139,32	149,44	167,37	181,88	201,57	228,22	257,50	291,10

