

JME120HC3N

Ambient Temp. (°C) (Dry Bulb temp.)	-25	-20	-15	-7	2	7	15	20	25	35	43
Heating Capacity (W) (Outlet Water Temp. 55°C)	5603	6513	7563	9419	11007	12358	13761	14920	16847	18200	19631
Heating Capacity (W) (Outlet Water Temp. 41°C)	5700	6750	7930	9940	12574	13617	14996	16287	17920	18983	20764
Heating Capacity (W) (Outlet Water Temp. 35°C)	5867	7210	8370	10571	13440	14892	16327	17862	18999	20481	21895
Power Input (W) (Outlet Water Temp. 55°C)	3367	3457	3514	3589	3621	3689	3752	3898	3941	3984	4023
Power Input (W) (Outlet Water Temp. 41°C)	2974	3141	3275	3504	3652	3724	3804	3846	3907	3866	3947
Power Input (W) (Outlet Water Temp. 35°C)	2801	2950	3208	3325	3485	3533	3649	3761	3856	3842	3907
COP (Outlet Water Temp. 55°C)	1,66	1,88	2,15	2,62	3,04	3,35	3,67	3,83	4,27	4,57	4,88
COP (Outlet Water Temp. 41°C)	1,92	2,15	2,42	2,84	3,44	3,66	3,94	4,23	4,59	4,91	5,26
COP (Outlet Water Temp. 35°C)	2,09	2,44	2,61	3,18	3,86	4,22	4,47	4,75	4,93	5,33	5,60
Water production(kg/h) (Water Temp. 15°C to 55°C)	120,44	140,00	162,58	202,47	236,61	265,65	295,81	320,72	362,15	391,23	421,99

