

JME50HC

Ambient Temp. (°C) (Dry Bulb temp.)	-25	-20	-15	-7	2	20	25	35
Heating Capacity (W) (Outlet Water Temp. 55°C)	1326	2071	2594	3381	4018	6010	6781	7580
Heating Capacity (W) (Outlet Water Temp. 41°C)	1580	2240	2770	3560	4279	6352	6904	7984
Heating Capacity (W) (Outlet Water Temp. 35°C)	1685	2390	3134	3897	4690	6511	7218	8306
Power Input (W) (Outlet Water Temp. 55°C)	994	1058	1117	1185	1247	1469	1475	1481
Power Input (W) (Outlet Water Temp. 41°C)	926	1024	1059	1123	1057	1243	1287	1311
Power Input (W) (Outlet Water Temp. 35°C)	817	947	982	1032	1098	1207	1266	1308
COP (Outlet Water Temp. 55°C)	1,33	1,96	2,32	2,85	3,22	4,09	4,60	5,12
COP (Outlet Water Temp. 41°C)	1,71	2,19	2,62	3,17	4,05	5,11	5,36	6,09
COP (Outlet Water Temp. 35°C)	2,06	2,52	3,19	3,78	4,27	5,39	5,70	6,35
Water production(kg/h) (Water Temp. 15°C to 55°C)	28,50	44,52	55,76	72,68	86,37	129,19	145,77	162,94

